



SOFTWARE MUTE SWITCH

PRODUCT DATASHEET



Description

The P2 Software Mute Switch is used to mute the current alarm from a Display unit. When the relevant RFID tag is presented to the Software Mute Switch it will activate the unit and mute the alarm coming from the connected Display unit. When activated, a ring of LEDs will illuminate red, shining through a rectangular window, and mute the alarm - this will also be confirmed on the Display unit's by a 'muted' icon on the screen.

Mounting

The Software Mute Switch should be mounted in a convenient place where it can be triggered if needed and associated to the equipment it is controlling as per containment specification and industry standards. Consideration should be given to the condition of the surface to which the unit is to be mounted: it should be free from damp and moisture, not be subject to any shock or vibration, and be secure enough to allow a good fixing for the Arm/Disarm Unit and box.

Design

The Software Mute Switch is designed to fit a standard single gang UK backbox. The fascia is a single piece designed to maximise durability; the main body is made from a Polycarbonate/ABS plastic blend with an inserted clear Polycarbonate indication window. All of the plastic utilised within the fascia has integrated Biomaster additive to destroy or inhibit the growth of a wide range of microbes, fungi and moulds over the entire lifespan or the product.

The unit is designed to be secured to the backbox using 30mm security screws which are countersunk into the fascia.

Specification

P2 Mute Unit Codes

P2 Software Mute Switch (Code: P2MUTESOF)

Physical Specification

Power Source: 12v to 13.8v DC
Current Drawn: 0.3A
Backbox: Single Gang UK
Weight: 67.6g

Physical Dimensions (All dimensions in mm)

